
HERITAGE ENVIRONMENTAL SERVICES, INC.





November 20, 1995

Mark A. Schollenberger
Environmental Protection Engineer
Illinois Environmental Protection Agency
Permit Section
Division of Land Pollution Control
2200 Churchill Road
Springfield, Illinois 62794



Dear Mr. Schollenberger:

As we discussed by telephone on November 14, 1995, enclosed are two additional copies of the tank integrity assessment report. This letter also serves to confirm your statement that the neither the tank integrity assessment report nor the containment coating assessment is required to be submitted. Accordingly, in the future these reports will only be maintained in the facility operating record.

Should you have any questions, require additional information, or wish to discuss this further, please contact the undersigned at (708)739-1151.

Sincerely,

HERITAGE ENVIRONMENTAL SERVICES, INC.

Ron Wilkins, CHMM Compliance Manager

cc: Angie Martin - Heritage Indianapolis Robert Garcia - Heritage Lemont

NOV 2 2 1995

RECEIVED

NOV 2 2 1995

REPA-BOL

PERMIT SECTION

4101RW95.L1






TABLE OF CONTENTS

Section	Page
Executive Summary	3
Site Map	9
Visual Site Inspection Form	10
Preliminary Assessment Form	24
Supporting Documentation	31

APPENDIX

TABLE OF CONTENTS

App	pend	<u>lix</u>	Page
	A	Illinois Location Map	A-1
	В	Site 4-Mile Radius and Surface Water Map	B-1
	C	IEPA Site Photographs	C-1

EXECUTIVE SUMMARY

Location

Petrochem Services, Incorporated can be found on Canal Bank Road N.E., Lemont, Cook County, Illinois which is between the Des Plains River and the Chicago Sanitary and Ship Canal. Petrochem maintains a 35 year lease with the Metropolitan Sanitary District of Greater Chicago. The 17 acre facility is located in the N1/2 of Section 21, Township 37 N., Range 11 E. of the 3rd P.M.

Current Operations

Petrochem Services, Incorporated is a service contracting company specializing in oil and chemical industry cleaning, maintenance and emergency spill response. This facility receives hazardous and non-hazardous wastes from off site and blends and treats these wastes to produce hazardous waste fuel, off-specification used oil and on-specification used oil (little to no on-spec used oil is generated). Sources of waste generated off site include cleaning tanker trucks and cleaning off site stationary tanks. This facility also operates an on site barge cleaning operation. They receive hazardous and non-hazardous wastes from the Illinois Environmental Protection Agency (IEPA Emergency Response Unit), the Illinois State Police Department of Criminal Investigations, Tox-Away (a government-sponsored Indianapolis, Indiana project to handle the shipment and disposal of hazardous household wastes) and generators, for temporary storage, which eventually go off site for incineration.

Permitting Status/History

Petrochem qualified for Interim Status by reporting that the construction of the facility began in May of 1980. IEPA Air Permit # 82110046 was issued July 6, 1984 while Operating Permit # 1983-5-OP was issued on August 24, 1984. In October of 1984, the first load was processed by the new facility. On April 2, 1985, ILWD purchased 50% of Petrochem stock which changed representation on the board of directors. As a result, on July 22, 1985, Petrochem started accepting solvents on a commercial basis and not just for emergencies as stated in the Operating Permit. Supplemental Permit # 1986-116-SP was issued July 17, 1986 only to be revised on August 28, 1987 and again of March 10, 1988. Currently, Heritage Environmental, Incorporated has sole ownership of

the facility and in April of 1989, Petrochem's name will be changed to reflect this.

SWMU Identification

Petrochem's facility consists of five Solid Waste Management Units (SWMU's). One SWMU was destroyed by fire and another is to be built sometime in the near future.

Tank Storage and Treatment Area

A major portion of wastes is processed in a 173.33 feet by 71.33 feet area that is capable of acid/chemical treatment, heat treatment, filtration, blending, agitation, flocculation, air flotation, dehydration, centrifuge, water treatment, carbon treatment, solidification, distillation, neutralization, fixation, emulsification, separation, and burning hazardous waste fuels and used oil fuel in the industrial boiler. The area is concrete diked to contain 110% of the total capacity of the 23 tanks involved in this SWMU.

Thirteen of the 23 tanks are used to treat oil/hydrocarbon mixes. These vessels recycle the oil-water mixture or the hydrocarbon-water mixture first by separation of the aqueous phases. This is accomplished by any of a number of the process listed above which will finally render the used oil into industrial fuel and the hazardous hydrocarbons into hazardous waste fuels. The aqueous phases are separated and disposed of as non hazardous or listed hazardous waste. The solids are dewatered and shipped to a landfill as hazardous or non hazardous.

Six tanks are designated for independent storage and or treatment. The vessels are used to store waste and perform basic treatment, such as, blending, decanting of aqueous phase, and filtration. Two of these tanks have side entry mixers to allow blending of various hazardous waste into hazardous waste fuel for licensed hazardous waste fuel burners. The other four tanks are used to store waste or recycled products. The waste may be hazardous or non hazardous and is either hazardous waste fuel blend stock or is accumulated for truckload shipments to recyclers or disposal sites.

The four other tanks inside the diked area include a lime slurry storage tank, two boiler fuel tanks and a recirculation tank. Two process water storage tanks are located just outside the diked area. The volumes of all of the tanks can be seen in the Visual Site Inspection Report.

The hazardous (restricted) wastes are generated at the rate of 45,000 gallons per month. This is shipped off site approximately 3 times per week to Continental Cement

(Hanibal, Missouri) or Systech (Greencastle, Indiana) for use as fuel in cement kilns.

Drum/Container Storage Area

Another SWMU is the drum/container storage area adjacent to the tank dike. The drums are stored for off site treatment/disposal or on site treatment by the preceding SWMU. The drum/container storage area is also diked so that 110% of the capacity of 600 drums would be contained. The unloading dock is designed so that any spills could be contained and collected by a sump built into the asphalt drive at the base of the dock.

Containerized Storage in Van Trailers

The area with containerized storage in van trailers is also considered a SWMU and is approximately 50 feet by 70 feet. This area can accommodate 10 trailers containing about 80 drums per trailer and is situated on an asphalt pad with a 2 to 3 inch berm.

Shredder Unit

A shredder unit operation that started in March of 1988 was destroyed by fire on September 1, 1988. The cause of the fire is unknown and Petrochem's insurance company is currently investigating. The SWMU consisted of a 160 drum storage with five 550 gallon process liquid waste storage tanks to facilitate the Shred-pax AZ-15 unit. Aerosol and non aerosol consumer products were processed by this unit.

Roll-Off Boxes

Two roll-off boxes are used to discard debris from the other SWMU's. The 15 and 20 cubic yard roll-off boxes are used to store recyclible metals or other trash.

Drum Crusher Unit

The drum crusher unit is used to reduce the volume of old drums that would go to a recycler. This unit is located near the roll-off boxes.

Hazardous Materials Present

Petrochem is permitted to accept a wide variety of wastes. An analysis of each waste stream accepted from each generator is to be maintained on file. The types of waste for recovery include: non-halogenated aliphatics; non-halogenated aromatics; alcohols; ketones; halogenated aliphatics; esters; corrosive waste; non-hazardous used, waste, off-spec and surplus oil; hazardous used, waste, off-spec and surplus oils; and listed hazardous petroleum refinery wastes. The

types of waste for blending into supplemental fuels include: non-hazardous used, waste, off-spec and surplus oils; hazardous used, waste, off-spec and surplus oils; non-halogenated solvents and liquids; and washes and sludges from the formulation of ink. Wastes for bulking and or blending consist of the following: non-halogenated solvents and liquids; and halogenated solvents and liquids. The wastes treated include: corrosive waste for neutralization and off-specification or scrap commercial products which were shredded. Wastes for crushing include, "RCRA Empty" contains. A complete list of wastes can be found in the attached supplemental permit.

Compliance History

The facility has had no major compliance problems. In the last inspection on September 30, 1988, the only deficiency noted was that containers of restricted hazardous waste were not marked to identify the date they entered storage.

Visual Site Inspection

At 1:00 pm on January 9, 1989, a visual site inspection was conducted by Tim Murphy and Rob Watson of IEPA. Petrochem was represented by Michael J. Crafton, plant manager and Paul Zajec, plant foreman. The weather conditions were clear and breezy with a temperature of 24 degrees Fahrenheit.

We first walked through the vehicle maintenance shop and on to the laboratory. The shop, as well as the laboratory appeared to be clean and organized. No analysis were being conducted at the time of our visit. From the laboratory we exited the building and stood in the truck transfer area. Although this area is to be a containment area should a spill occur, we noticed the area was fairly level. We proceeded to walk around the tank process storage and treatment unit and discussed some of the processes. No cracks were noted in the 5 foot dike that surrounded the tanks. We continued on and inspected the drum/containerized storage area and the containerized storage in van trailer area. Southwest of the van trailer storage area, we saw where the shredder unit had been destroyed by fire. The debris from the fire had been cleaned up and removed or stored in the north corner of the property.

Drainage for the balance of the property is to the canal either by direct gradient or by a small ditch on the western portion of the property. The ditch could be blocked off in the event of a mishap. The capacity of the ditch is several thousand gallons.

Next, we looked at an area south of the main processing SWMU and northeast of the burned shredder unit where a new treatment system is to be built. Rob Watson who is reviewing

the permit for the fixation unit, wanted to look at the location. The inspection ended at 3:00 pm after a question and answer session in the offices.

Site Releases/Sampling

No samples have ever been taken of Petrochem's facility and a file review has come up with no complaints. There has been three reported minor releases, one release to the Canal and two air releases. On February 19, 1985, 150-200 gallons of 28% caustic was lost to the Sanitary and Ship Canal when a barge hose ruptured. A 95% clean-up was reported. In July of 1988, a reaction in a trailer sent approximately 5 pounds of lithium aluminum hydrate into the air. The other air release occurred in the September 1, 1988 shredder unit fire.


Targets

In a four mile radius of Petrochem, there are 19 public water wells. The nearest well is one mile south of the site in the village of Lemont. The well is one of three wells that supply the 5640 citizens of Lemont. The well is open from 128 feet to 241 feet in the fractured dolomite aquifer continuous with the aquifer underlying Petrochem. The other two wells are about a mile and a half away and are open in the deeper sandstone aquifer as are many of the other wells in the surrounding area.

Nearby surface waters in the area consist of the Sanitary and Ship Canal that bounds the southwest and southeast side of the property and the Des Plaines River. According to a recent Flood Insurance Rate Map of Cook County Illinois, Petrochem is located in an area of minimal flooding. A 100 year food plain exists on the other side of the Des Plaines River. No public surface water intakes are located downstream.


Air releases are documented and have been discussed in the preceding section. Other than the two reported incidences, no ongoing air pollution episodes were noticed. The area within a half mile of the site is almost entirely industrialized.

The direct contact route is held in check by and 8 foot fence around the site with the exception of the canal and barge slip areas were a 5 foot shear would be encountered.



USGS Topographic Series: Romeoville, IL and Sag Bridge, IL (53A revised 1980, 54B photorevised 1978)

Scale: 1 inch equals 1/4 mile



VISUAL SITE INSPECTION REPORT

FACILITY VISUAL SITE INSPECTION FORM

Facility Name: Petrochem	Services, INC. EPA I.D. N	umber: 1LD 085 349264
Location Address: Canal B	ank Rd. N.E. TOD Number	CONTRACTOR OF
Lemont, 11 60439 (C	ook County) HSTS Number	
Facility Contact/Title: Mic	hael J. Crafton, Plant A	Nanager
Phone Number: (312) 739-115		
Date of Inspection: January	9, 1989 Time of In	spection: 13 oo
Weather: clear, breezy		
Person(s) Interviewed	Organization	Title
Michael J. Crafton	Heritage Environmental	Plant Manager
	Services, Inc.	90
Paul Zajec	Petrochem Services, INC.	Plant Foreman .
Inspector(s)	Organization	Title
Timothy J. Murphy	IEPA Remedial Project Management Section	Environmental Specialist
Rob Watson	IEPA Permit Section	Environmental Engineer
Facility Description: Petro c	hem Services, INC. is a serv	ice contracting
Company Specializing in oi	I and chemical industry clear	ring, maintenance
	ise. The facility engages in w	
	f hazardous and Non hazardou	
in the production of recyc	led materials, fuels, hazardous	waste fuels, off
spec oil and enhanced d	isposal streams. Petrochem a	lso serves as a
	arketer and burner of haza	
The facility consists of	corperate offices, a 70'x	100' vehicle mainten-
	, a 130' truck transfer and o	
a 173.33' × 71.33' 23 -	tank Storage and treatmen	st area, 2 28,481 gallon
water storage tanks, a	30.67' x 71.33' 600 drum s	storage area, 1

4. Visual Site Inspection (VSI)

A .	specific Objectives: 15 cubic yard and 1 20 cubic yard storage roll-off boxes, a 10 van trailer storage area, a plate and frame filter press unit, 2 heat exchangers, a boiler, a drum crusher, and all corresponding sumps, pumps, piping controls, filters, and appurtenances. Petrochem also had a Shed-pax AZ-15 shredder with conveyors, fire suppression, exhaust and liquid collection system which had a 160 drum storage area and 5 550 gallon process liquid waste storage tanks. This system burned up Sept. 1, 1988.
	roll-off boxes a 10 van trailer storage area a plate and frame
	filter press unit. 2 heat exchangers, a boiler, a drum crusher
	and all corresponding sumps pumps piping controls filters.
	and appurten airces. Petrochem also had a Shed-pax AZ-15
	shredder with conveyors, fire suppression, exhaust and liquid collection
	system which had a 160 drum storage area and 5 550 gallow process
	liquid waste storage tanks. This system burned up Sept. 1, 1988.
	10.00 m

SHMU No .: 1 Type: Tank Storage and Treatment Area
Unit Description: The 23 storage tanks or vessels used at the
facility are constructed of materials compatible with materials held in
storage. The vessels are located inside of a concrete dike designed
to contain 110% of the total capacity of all vessels. Processes include
acid/chemical treatment, heat exchanger, filtration, blending, agitation
flocculation, air floatation, dehydration, centrifuge, water treatment,
carbon treatment, solidification, distillation, neutralization, fixation,
emulsification, separation, and burn hazardous waste fuels and used
oil fuel in the industrial boiler. A list of the tanks is on the
following page.
Date of Start Up: 8-24-84
Date of Closure: active
Method of Closure:
Waste Description: A wide variety of wastes are processed at this
SWMUs these included the following listed on the supplemental
permit attached in the supporting documentation (002 page 47)

Tank Designation	Volume Per Tank (Gals.)	<u>Usage</u>
ST-1	7,686	Waste/Product Storage and Fuel Blending
ST-2	10,380	Waste/Product Storage and Fuel Blending
ST-3	11,177	Waste/Product Storage and Fuel Blending
ST-4	10,981	Waste/Product Storage and Fuel Blending
ST-5	7,686	Waste/Product Storage and Fuel Blending
ST-6	7,686	Waste/Product Storage and Fuel Blending
0S-1	62,375	Waste/Product Oil Storage
0S-2	62,375	Waste/Product Oil Storage and Fuel Blending
HT-1	19,828	Heat/Treatment and Waste/Product Oil Storage
HT-2	19,828	Heat/Treatment and Waste/Product Oil Storage
HT-3	19,828	Heat/Treatment and Waste/Product Oil Storage
HT-4	19,828	Heat/Treatment and Waste/Product Oil Storage
CB-1	21,401	Oily Waste Treatment/Holding Tank
CB-2	21,401	Oily Waste Treatment/Holding Tank
CB-3	21,401	Separated Water Treatment Tank
CB-4	21,401	Sludge/Water Holding Tank
VR-1	5,875	Waste Storage
VR-2	5,287	Waste Storage
VR-3	5,287	Waste Storage
LS-1	10,528	Lime Slurry Storage Tank
BFS-1	17,000	Boiler Fuel Storage Tank
BFS-2	1,500	Boiler Fuel Storage Tank
RT-1	5,875	Recirculation Tank

SWMU No.: 2		-	Type: _	600	Drum	Stor	age Area
Unit Description:	The	drum	area is	also	diked	with	concrete and
is attached to	the	Tank	Storage	and	Treat	ment	Area.
Wash Wall							
							September 1
					28.5		
Date of Start Up:	8	3-24-	84				A SECTION AND SECTION
Date of Closure:		active					
Method of Closure:							
The chief of the chief							
							- 1227 A. A.
Wasta Dassrintian:	All	4	44		elan		which to a 1 1:1:1
							ubject to compatability
See the attach	200 5	appleme	enter per	rmit	(Page	41)	
		mp.					
		*			Richard Son	AL PROPERTY OF	

SHMU No.: 3 Type: Containerized Storage in Van Trailers
Unit Description: This unit is southwest of the 600 drum storage
area and consists of an asphalt pad with a 2 inch berm that
will hold 10 trailers with approximately 80 drums pertrailer.
The area is about 50' x 90'.
· · · · · · · · · · · · · · · · · · ·
Date of Start Up: March 10,1988
Date of Closure: active
Method of Closure:
Waste Description: Same as SWMU I and 2

SWMU No.: 4 Type: Shedder Unit
Unit Description: Shed-pap AZ-15 with 160 drum storage and 5 550
gallon process liquid waste storage tanks
Date of Start Up: March 1988
Date of Closure: Sept. 1, 1988
Method of Closure: Burned up, Insurance company is investigating.
At this time, cause of fire is still unknown.
What Description ()
Waste Description: Consumer products (acrosol cans, etc.)

SWMU No.: 5			ype: Roll	- off boxe	25	
Unit Description:	ONE	15 cu	bic yard	and on	1 20 eubic	yard
(see pictures)						
Date of Start Up:	UNKNOW	14				
Date of Closure:	active					
Method of Closure:						
	- 200	F Lake S	4 2 2 3			
Wasta Dasswintian.	1E1		1 1 11		1.1. 0. 1.	
Waste Description:			a hold 5	metals w	hile 20 cubi	c yard
holds misculariou	16 aebri	\$				

SWMU No.: 6		Type:	drum	crushe	-		
Unit Description:	(see pic	cture)	Alexander and				
					At the second		
							And I
Date of Start Up:	UNKNOWN						
Date of Closure:							
Method of Closure:							
	A STATE OF THE STA					- M. J. F. A	
Waste Description:	drums	that wil	I an to	me to 1	recirler		
			90	7.0.07	recycler		
		100 2					

EPA Waste Number:
Release Controls: A 5' dike exist around the 23 Tank Storage
and Treatment area as well as the 600 Drum Storage area which
enable these areas to hold 110% of thier total volumes. Certain
tanks and vessels in the Tank Storage and Treatment area are equipe
with relief valves that pass vapors through a carbon absorber control
device prior to release. The central drainage ditch that enters the
canal can be blocked to intercept a spill.
History of Release: ON 2-19-85, 150-200 gallons of 28% caustic
was lost to the Sanitary and Ship Canalwhen a barge hose ruptured
They reported 95% clean-up. In July of 1988, a reaction in a
trailer sent approximately 5 pounds of lithium aluminum hydrate
into the air. On September 1, 1988, the Shedder Unit fire created
another air release.
Observed/Potential Poloaces
Observed/Potential Releases Soils: No Soils axist and Site The site at the distribution of the site o
Soils: No soils exist on site. The site sits directly on top
of Niagaran dolomite. No observed releases were noted.
Croundyston: Although the Min all it I C I
Groundwater: Although the Niagaran dolomite has fractures, the
diked areas would not permit such a release.

Air: Other than the July and September 1988 releases, No
visual or olfactory releases were noted
Subsurface Gas: None Noted
Surface Water: Nove Noted
Exposure Potential
Direct Contact: The exposure potential via direct contact is minimized
by a 8 foot fence around the site other than the Canal and
barge slip areas where a 5 foot shear would be encountered.
Groundwater Route: One mile south of the site alemont public well
is open to the Niagaran dolomite (uncased from 128'-241')
continuous with the aquifer underlying petrochem

Air Route: Within 1/2 mile of the site, there are few residential
dwellingsbut within 4 miles of the site, there are greater than
10,000 people
Sensitive Environments: None Noted .
Suggested Further Act: RCRA inspections should continue
Suggested Fultiles Act. NERN INSPECTIONS SHOULD CONTINUE

Evaluation Summary: Petrochem Services, Inc. generates about
45,000 gallons of hazardous waste fuel (Doo1, FOO3, FOO5)
per month. Since the facility started accepting waste in
1984, only three minor releases have occurred. Overall, the
facility is operating within RCRA regulations. Routes of
Contamination have been held in check by dikes, berms and
air filtration consisters on certain vessels. Under CERCLA, the
facility does not warrent a Screening Site Inspection

TJM:jab/sp87k

L0311620007



NFA-SSW Yorksa

\$EPA

POTENTIAL HAZARDOUS WASTE SITE PRELIMINARY ASSESSMENT PART 1 - SITE INFORMATION AND ASSESSMEN

I. IDENTIFICATION

OI STATE OF SITE NUMBER

ILD OBS 349264

PART 1 - SITE INFORM	ATION AND ASSESSMENT					
II. SITE NAME AND LOCATION						
01 SITE NAME (Legal, common, or descriptive name of site)	02 STREET, ROUTE NO., OR SPECIFIC LOCATION IDENTIFIER					
Petrochem Services, Inc.	Canal Bank Road N.E. (P.O. Box 337)					
03 CITY	04 STATE 05 ZIP CODE 06 COUNTY 07 COUNTY 08 CON CODE DIST					
Lemont	1L 60439 Cook 031 0857					
09 COORDINATES LATITUDE LONGITUDE	Sag Bridge, IL					
41 42 00.5 088 59 10.0	N4137.5 - WE152.5/75 54B					
10 DIRECTIONS TO SITE (Starting from nearest public road)	Emiles to Coul & de A I NEC I I					
site is located 2.5 mile east of Lemont Road and Ship Canal and the Des Plains River	.5 miles to Conal Bank Road N.E. (gravel road) (Stephen St.) between the Chicago Sanitory					
III. RESPONSIBLE PARTIES						
01 OWNER (If known)	02 STREET (Business, mailing, residential)					
Heritage Environmental Services, IN	c 7901 West Morris Street					
Indianapolis	04 STATE 05 ZIP CODE 06 TELEPHONE NUMBER (317) 243-0811					
07 OPERATOR (If known and different from owner)	08 STREET (Business, mailing, residential)					
09 CITY	10 STATE 11 ZIP CODE 12 TELEPHONE NUMBER					
	()					
13 TYPE OF OWNERSHIP (Check one)						
A. PRIVATE B. FEDERAL: (Agency name)	□ C. STATE □D.COUNTY □ E. MUNICIPAL					
☐ F. OTHER:	G. UNKNOWN					
(Specify) 14 OWNER/OPERATOR NOTIFICATION ON FILE (Check all that apply)						
	LLED WASTE SITE (CERCLA 103 c) DATE RECEIVED: / / MONTH DAY YEAR					
IV. CHARACTERIZATION OF POTENTIAL HAZARD						
01 ON SITE INSPECTION BY (Check at thet apply)	DA CONTRACTOR					
■ YES DATE 10 , 27 , 81 □ A. EPA □ B. E □ NO MONTH, DAY YEAR 3 , 28 , 86	PA CONTRACTOR					
9/30/88 6/28/88 CONTRACTOR NAME(S):	(Specify)					
	· · · · · · · · · · · · · · · · · · ·					
02 SITE STATUS (Check one) 103 YEARS OF OPE 103 YEARS OF OPE 104 A. ACTIVE B. INACTIVE C. UNKNOWN	BEGINNING YEAR ENDING YEAR					
04 DESCRIPTION OF SUBSTANCES POSSIBLY PRESENT, KNOWN, OR ALLEGED						
This RCRA regulated facility accepts a wide	variety of used oils, sludges, solvents, etc. for					
treatment						
05 DESCRIPTION OF POTENTIAL HAZARD TO ENVIRONMENT AND/OR POPULATION						
None Not	ed or observed					
None none						
V. PRIORITY ASSESSMENT						
01 PRIORITY FOR INSPECTION (Check one. If high or medium is checked, complete Part 2 · Waste Information and Part 3 · Description of Hazardous Conditions and Incidents)						
A. HIGH (Inspection required promptly) B. MEDIUM (Inspect on time available basis) D. NONE (Inspect on needed, complete current disposition form)						
VI. INFORMATION AVAILABLE FROM						
01 CONTACT 02 OF (Agency/Organ						
Michael J. Crafton Heritage	Environmental Services, INC. (3171243-0811					
04 PERSON RESPONSIBLE FOR ASSESSMENT 05 AGENCY	06 ORGANIZATION 07 TELEPHONE NUMBER 08 DATE					
Timothy J. Murphy IEPA	RPMS 1217 1785-5737 1,9,89					
EDA FORM 2020 4 0 /2 0 M	MONTH DAY YEAR					

IV. HAZARDOUS SUBSTANCES (See Appendix for most frequently cried CAS Numbers

CATEGORY	—	03 CAS NUMBER	04 STORAGE DISPOSAL METHOD	05 CONCENTRATION	06 MEASURE O
OLW	oil/water separat or wastes			1	
OLW	bilge oil wastes				
OLW	oily wash waters from cleaning				
OLW	spill clean-up residues				
OLW	pipeline interfaces and transmixes				
SOL	Mineral Spirits				
SOL	Naptha s				
SOL	paraffin solvents				
SOL	plasticizers				
Soi	Styrene				Total State
	jet fuel				
SOL	10				To the second
SOL	gasoline				
SOL	heptane	110007			
SOL	cyclohexane	110827			
SOL	hexane				100
SOL	Kerosene				
SOL	lacquer thinner				
SOL	stoddard's solvent		1 Storage		
SOL	turpentine		2 treatment		
SOL	iso prede	78795	3 blending into fuels		
SOL	pentane		4 recycling		
SOL	hexene's		5 blending for off-		
SOL	isopentane		site incineration		
SoL	methyl cyclohexane		6 Shredding for		
SOL	isoctane		Volume reduction		
SOL	tetrachloroethy lene	127184			
SOL	trichloro ethylene	79016			
SOL	methylene chloride	75092			
	1,1,1, -trichloroethane	71556	REMARKS AND THE SECOND		The last
SOL	earbon tetrachloride	56235		- Carlotte - 1872 - 25	
SOL					
SOL	chlorinated fluorocarbons				
SOL	chlorobenzene	108907			
SOL	1,1,2-trichloro-1,7,2-trifluoroethane	76131			
50L	orthodichlorobenzene			Tar San	
SOL	trichloro flaoromethane	75694			
SOL	dichloro berizene	25321276			
SOL	xylene				
SOL	benzene	71432		A STATE OF	
SOL	toluene				
SOL	Cumere	98828			
SOL	cresols	1319173			
SOL	cresylic acid	1319773			
SOL	Nitrobenzene		The second secon		Barry Blatt
SOL	ethyl benzene	100 414			
		141 786			
SOL	ethyl acetate	111700			1
SOL	vinyl acetate				
SOL	dioctyl phthalate				

IV. HAZARDOUS SUBSTANCES (See Appendix for most frequently cred CAS humbers

O1 CATEGORY		03 CAS NUMBER	0	4 STORAGE DISPOSAL METHOD	05 CONCENTRATION	06 MEASURE CONCENTRATION
SOL	Methyl acetate		1			
SOL	isobuty1 acetate					
SOL	isopropy/ actate				TAKINE DAY	
SOL	isoamyl acetate	123922				
SOL	amyl acetate	628637				
SOL	ethyl meth yl acrylate				A TOTAL ORDER	
SOL	ethyl acrylate	140885				
SOL	ethanol		10			ASS
SOL	ethylene glycol					
SOL	butanol	71363				
SOL	isobutyl alcohol	78831				
502	methanol				THE PARE NO	
SOL	isoamyl alcohol					
SOL	tert amyl alcohol	3 5000 1000				
SOL	cyclohex anol					6 B
SOL	diacetone alcohol					
SOL	Z-ethyl-1-butanol					
SOL			1			
SOL	2-ethyl-1-hexanol ethyl butanol		+	1 Storage z treatment		
SOL	isopropyl alcohol					
SOL	2-methyl-2-butanol			3 blending into fuels		
SOL			+	4 recycling		
SOL	propanol	70021	+	5 blending for off-		
SOL	2-methyl-1-propanol N-octanol	78831	+	site incideration		
SOL	a cetone	67641	-	6 Shredding for volume reduction		
SOL	methyl ethyl ketonie	18933	+	reduction		
		108191	+			
SOL	Methyl isobutyl ketone	Inglal	1			
SOL	diacetone alcohols	9888Z	+-			
SOL	acetophenone	10007	+			
SLU	disobutyl ketones DAF float - KO40					
			-			
SLU	Slop oil emulsion solids - Ko49					96
SLU	heat exchange bundle cleaning					
	Sludge - KOSO					
524	API separator (leaded)-Ko51					
SLU	tank bottoms (leaded) - KO52.					
SLU	ink formulation waste-K086					
and the second s	sodium hydroxide	1310732				
	potassium hydroxide					
BAS	wastewaters and bottoms containing					
	NaCH and KOH					
ACD	Sulfuric acid					
	phosphoric acid					
ACD	wastewaters and bottoms containing					
	sulfuric and phosphoric acid		/			
occ	Soaps and detergents		1			
BAG	alkaline cleaners					
	air freshwers					

IV. HAZARDOUS SUBSTANCES (See Appendix for most frequently cited CAS Numbers

CATEGORY	02 SUBSTANCE NAME	03 CAS NUMBER	0	4 STORAGE DISPOSAL METHOD	05 CONCENTRATION	06 MEASURE (
oce	health and beauty aids)
occ	petroleum products			Shedder system only		
occ	food products			y storry stry		
occ	prints and related and the	11				
occ	paints and related products adhesives			Processing the second		
OCC	cement					
occ	insulation		17			
	creosote		1			
501	1-3 6 bille alicel		1-2			
Co	1-3 butylene glycol		-	2		
SOL	propylene glycol	/2.22		Storage		
	chloro-form	67683	-	recycling off-site incineration		
SOL	perchloroethy leve		-	ott - site incineration		
SOL	1, 1, 2-trichloro ethane	1	-			
Sol	di methy l- phthalate	131113	1			
SOL	di-N-but phthalate	84742	1		AT TEMES	
1 to 1						
					arries	
900 45						
		14.00	1			
			-			
			-			
			-			
			-			
			-			
		-				
			-			
400			1			
The state of						
			1			
			-		100.178	
			-			
						2 2
			-			
			_			
					NAME OF BUILDING	A COLOR
			-			
					PRINCIPLE TO SELECT THE PARTY OF THE PARTY O	

POTENTIAL HAZARDOUS WASTE SITE

I. IDENTIFICATION 01 STATE 02 SITE NUMBER

PART 3 DESCRIPTION	OF HAZARDOUS CONDITIONS AND INCI	DEM 12		
. HAZARDOUS CONDITIONS AND INCIDENTS				
01 A GROUNDWATER CONTAMINATION 03 POPULATION POTENTIALLY AFFECTED: None Noted or observed		,	POTENTIAL	ALLEGED
01 0 B. SURFACE WATER CONTAMINATION 03 POPULATION POTENTIALLY AFFECTED: None noted or observed	02 C OBSERVED (DATE:04 NARRATIVE DESCRIPTION)	L: POTENTIAL	ALLEGED
01 [] C. CONTAMINATION OF AIR 03 POPULATION POTENTIALLY AFFECTED: None Noted or obse		.)	. POTENTIAL	C' ALLEGED
01 © D. FIRE/EXPLOSIVE CONDITIONS 03 POPULATION POTENTIALLY AFFECTED: NONE Noted or obs	02 - OBSERVED (DATE:	_)	C POTENTIAL	□ ALLEGED
	04 NARRATIVE DESCRIPTION	_1	C POTENTIAL	. ALLEGED
03 POPULATION POTENTIALLY AFFECTED: NONE NOTED OF SOIL 03 AREA POTENTIALLY AFFECTED: (Acres)	02 OBSERVED (DATE O4 NARRATIVE DESCRIPTION	. 1	POTENTIAL	ALLEGED
03 POPULATION POTENTIALLY AFFECTED	02 OBSERVED (DATE O4 NARRATIVE DESCRIPTION	. 1	POTENTIAL	ALLEGED
03 POPULATION POTENTIALLY AFFECTED: NONe Noted or 01 [] F. CONTAMINATION OF SOIL 03 AREA POTENTIALLY AFFECTED: No soil exists on site, facility sin deposit	02 DOBSERVED (DATE DATE DATE DATE DATE DATE DATE DATE	dolom	POTENTIAL	ALLEGED
01 [] F. CONTAMINATION OF SOIL 03 AREA POTENTIALLY AFFECTED: No soil exists on site, facility sind deposit 01 [] G. DRINKING WATER CONTAMINATION 03 POPULATION POTENTIALLY AFFECTED	02 [] OBSERVED (DATE	dolom	. POTENTIAL ite and so	ALLEGED wid stone

EPA FORM 2070-12(7-81)

Supporting

Documentation

Number	Document	Page
001	Operating Permit # 1983-5-OP	33
002	Supplemental Permit # 1986-116-SP	47
003	Summary of 9-30-88 Inspection	65
004	Parts of IEPA DLPC File L0311620007	66
005	Flood Plain Insurance Map	68



Petrochem Services, Inc.

P.O. Box 337

Lemont, Illinois 60439

(312) 739-1150

February 25, 1988

Illinois EPA
Division of Land Pollution Control
2200 Churchill Road
P.O. Box 19275
Springfield, IL 62794-9276

Attention: Mark Scholenberger

Reference: Revised Part A for Petrochem Services, Inc.

Dear Mark Scholenberger:

Enclosed please find a revised RCRA Part A Application for Petrochem Services, Inc. This revision is made in response to USEPA recommendations that this Part A Application be utilized in accordance with the procedures outlined in 40 CFR Part 270.72 (b) and (c).

It is further understood that no additional public notification is required for Petrochem Services, Inc. to change the volumes associated with tank storage capacities.

If you should have any questions or need additional information please feel free to call.

Sincerely,

Mark Schiefelbein Technical Services

MS: lw

Enclosure

cc: USEPA Region V, w/Enclosure

RECEIVED

MAR 1 1988

IEPA-DLPC

CONTINUED FROM THE FRONT	
VII. SIC CODES i4-digit, in order of priority	the same of the sa
A. FIRST	A. SECOND
7 4 4 6 0 specify.	(specify)
13119 : 19	7
C. THIRD	D. FOURTH
	7 (specify,
VIII OPERATOR INFORMATION	13 19 19
THE OPERATOR INFORMATION	entained the production of the
e	B. Is the name listed
SPETROCHEM SERVICES, I	
18 10	₩ YES NO
C. STATUS OF OPERATOR (Enter the appropriate letter is	into the answer box: If "Other" made.
S = STATE	D (ispecify)
P - PRIVATE	A 3 1 2 7 3 9 1 1 1 5 0
E. STREET OR P.O. BOX	115 16 - 16 19 - 37 13 - 18
P. O. B O X 3 3 7	
16	30/
F. CITY OR TOWN	G.STATE H. ZIP CODE IX, INDIAN LAND
BITEMONE	Is the facility located on Indian lands?
1. E. M.O.N.T.	11.116.0.4.3.9 TYES TO NO
X EXISTING ENVIRONMENTAL PERMITS	46 49 42 47 - 11
A. MPOES (Discharges to Surface Water) D. PSD /A	tir Emissions from Proposed Sources;
STATE OF THE STATE	TTTTTTTTTTTTTTTTTTTTTTTTTTTTTTTTTTTTTT
9 N N/A 9 P	
B. UIC (Underground Injection of Fluids)	E. OTHER (specify)
9 U N/A	2 d 9 O C A A T 1 1 (enecifu)
11 16 17 19	3 1 8 0 6 A A Y ILLINOIS AIR PERMIT
C. RCRA (Hazardous Wastes)	E. OTHER (specify)
9 R; T. D. D. O. S. S. D. O. C. S. D. D.	(specify)
17 ! (4 ! 14 17 14	3.1.1.6.2.0.0.0.7. ILLINOIS LAND PERMIT
XL MAP	Commence of the second
Attach to this application a topographic map of the area ex	ktending to at least one mile beyond property boundaries. The map must show
treatment, storage, or disposal facilities and each well who	is in its hazardous waste
water bodies in the map area. See instructions for precise rec	quirements.
XIL NATURE OF BUSINESS (provide a brief description)	
Petrochem Services Inc is a service	contracting company or and
industry cleaning maintenance and emaintenance	contracting company specializing in oil and chemical ergency spill & sponse. The Facility engages in
Various storage & treatment technologi	ies of hazardous & non hazardous waste which results
in the production of recycled material	ls, fuels, hazardous waste fuels, off spec oil and
enhanced disposal streams. Petrochem	also servies as a Generator, Transporter, Marketer
and burner of hazardous waste fuels.	albo servies as a denerator, fransporter, marketer
The state of the s	
(III. CERTIFICATION (see instructions)	
attachments and that haved on my inquiry of the	ned and am familiar with the information submitted in this application and all
application. I believe that the information is the	in interesting responsible for obtaining the information contained in the
talse information, including the possibility of fine and imprise	conment.
. MAME & OFFICIAL TITLE (Type or print)	SIGNATURE
George A. Smith	1 C. DATE SIGNED
	Groryc H, Smilts V. Pm 2/24/88
NTS FOR OFFICIAL USE ONLY	AND THE RESIDENCE OF THE PARTY
16	
Form 3510-1 (6-80) REVERSE	

Please print or type in the unshade (fill—in areas are spaced for elice to		finch).		Form Approved OM8 No. 158-580004
3 ⊋EPA	HAZARDOU	S WASTE PERM Consolidated Permit	MIT APPLICATION	I. EPA I.D. NUMBER
RCRA			Section 3005 of RCRA.	FILLD085349264
FOR OFFICIAL USE ONLY		Profession and	THE PERSONAL PROPERTY.	and the second the second second
APPROVED IN TO S day	,0		COMMENTS	
13 10	10			
II. FIRST OR REVISED APP	STATE OF THE PARTY		(1891)。	企業的企业。
Place an "X" in the appropriate bo revised application. If this is your EPA I.D. Number in Item I above.	in A or B below (ma first application and ye	ork one box only) to a	ndicate wnether this is the first r facility's EPA I.D. Number, o	t application you are submitting for your facility in if this is a revised application, enter your facility
A. FIRST APPLICATION (Pla	ce an "X" below and a	rouide the appropria	te date)	
1. EXISTING FACILITY		efinition of "existing		2.NEW FACILITY (Complete item below FOR NEW FACILI
O CO COPI	R EXISTING FACILITERATION BEGAN OR the boxes to the left)	THE DATE CONST	DATE (yr., mo., & day) RUCTION COMMENCED	PROVIDE THE DAY (yr., mo., å day) OF TION BEGAN OR EXPECTED TO BE
B. REVISED APPLICATION		nd complete Item I a	boue)	2. FACILITY HAS A RCRA PERMIT
III. PROCESSES - CODES AL	ND DESIGN CAPAG	CITIES	ate to be sent the book	THE CONTRACTOR OF THE CONTRACT
			t has describer such assess	be used at the facility. Ten lines are provided
describe the process (including i	a needed, enter the codits design capacity) in t	de(s) in the space pro the space provided on	vided. If a process will be used the form (Item III-C).	that is not included in the list of codes below, t
B. PROCESS DESIGN CAPACITY 1. AMOUNT - Enter the amount 2. UNIT OF MEASURE - For	unt.			measure codes below that describes the unit of
measure used. Unly the unit	is of measure that are l	isted below should be	used.	
PROCESS	CESS MEASURE	FOR PROCESS	2000000	CESS MEASURE FOR PROCESS
Storage:	CODE DESIGN	CAPACITY	PROCESS Treatment:	CODE DESIGN CAPACITY
CONTAINER (barrel, drum, etc.)	SOI GALLONS O	RLITERS	TANK .	THE GALLONS PER DAY OR
WASTE PILE	SOS CUBIC YARI	DSOR	SURFACE IMPOUNDMEN	The second of the second
SURFACE IMPOUNDMENT	504 GALLONS O		INCINERATOR	TOS TONS PER DAY TONS PER HOUR OR METRIC TONS PER HOUR:
Disposal:	D79 GALLONS O	RLITERS		GALLONS PER HOUR OR LITERS PER HOUR
LANOPILL	would cover o		thermal or biological treatm	ent LITERS PER DAY
LAND APPLICATION	depth of one HECTARE-M D81 ACRES OR H	ETER	processes not occurring in t surface impoundments or in ators. Describe the process	Iciner RECEIVED
OCEAN DISPOSAL	DAZ GALLONS PE	ER DAY OR	the space provided: Item II	I-C.)
SURFACE IMPOUNDMENT	D83 GALLONS O	RLITERS		MAR 1 1988
UNIT OF MEASURE	UNIT OF MEASURE		UNIT OF MEASURE	UNIT OF MEASURE
GALLONS		LITERS PER DAY	CODE	
CUBIC YARDS			0	ACRE-FEET
GALLONS PER DAY	c	GALLONS PER HOL		ACRES
EXAMPLE FOR COMPLETING IT	EM III (shown in line n	rumbers X-1 and X-2	helowl: A facility has non es	prage tanks, one tank can hold 200 gallons and ti
11	lity also has an inciner	rator that can burn up	to 20 gallons per hour.	
C DUP	13 14 19			1111111111
	DESIGN CAPACIT		MIA. PRO-	OCESS DESIGN CAPACITY
CESS CODE	10	Z. UNIT OFFICIAL	W CESS	2. UNIT OFFIC
WE CODE	00111	SURE ONLY	ZO (from list	1. AMOUNT SURE USE
X-1 S 0 2 600	17	20 10 · 12	110 - 110	i code,
W 2 2 2 2 2			5 1 1	
X-2T 0 3 20		E	6	
85,800		G	7	
2 sio 2 435 734 354,861		l _G	8	
3 T 0 1 45,000			9	
4 704 50,000		III IIII	10	
EPA Form 3510-3 (6.80)		The state of the s		

- EPA I.O. NUMBER (enter from page 1)	POR OFFICIAL USE	ONLY !
W 1: 1 - 1 4 5 1 4 7 1 1	DUP	2 DUP
PESCRIPTION OF HAZARDOUS WAST	(ES (continued)	
A. EPA W. HAZARO. J. WASTENO GO (enter code) GO (enter code)	C.UNIT OF MEA- SURE (enter 1. PROCESS CODES	D. PROCESSES
12 10 11	COGET	(If a code is not entered in D(1))
1 F 0 1 2500	T S 0 1 S 0 2 T 0 1 T 0 4	
2 F 0 0 2 2500	T S 0 1 S 0 2 T 0 1 T 0 4	
3 F 0 0 3 2500	T S,0,1 S,0,2 T,0,1 T,0,4	
4 0001		Included with above
5 F 0 0 5 2500	T S 0 1 S 0 2 T 0 1 T 0 4	
6 D O O 1		Included with above
7 K 0 4 8 400	T S O 1 S O 2 T O 1 T O 4	
8 D O O 8		Included with above
9 K 0 4 9 1000	T S01S02T01T04	
10 D 0 0 8		Included with above
11 D O O 1		Included with above
12 D O O 3		Included with above
13 K 0 5 0 100	T S 0 1 S 0 2 T 0 1 T 0 4	
14 D 0 0 8		Included with above
15 K 0 5 1 1000	T S 0 1 S 0 2 T 0 1 T 0 4	
16 D 0 0 8		Included with above
1/ DO 0 1		Included with above
18 K 0 5 2 400	T S 0 1 S 0 2 T 0 1 T 0 4	
19 D 0 0 8		Included with above
20 D 0 0 1		Included with above
21 U 0 0 2 87	T S 0 1 S 0 2 T 0 1 T 0 4	
22 D O O 1		Included with above
23 11 0 3 1 35	T S 0 1 S 0 2 T 0 1 T 0 4	
24 D O O 1		Included with above
25 1 9 35	T S 0 1 S 0 2 T 0 1 T 0 4	30000
26 000 1	1111111	Included with above
"A Form 3510-3 (6-80)	n v · n v · · · · · · · · · · · · · · ·	CONTINUE ON REVERSE
	PAGE 3 A OF 5	

	-	A	.0.	NUI	MBER lenter from page 11	1		L		I			0	• 13	PPI	CIA		***	ONLY
W	1	.	-1	-10	52.0264	/	1	*	1.				D	U	P				DUP
	PE			-	ON OF HAZARDOUS WAST	-	OAN	7	.11	×			が		£3.			-	D. PROCESSES
ZI.	W	LAN	TA	RD.		100	HEA Her Hal				1. **	10	nte	r)					2. PROCESS DESCRIPTION (If a code us not entered in D(1))
1		1	Ta	To	137	1		S	0) 2	2 1	0 2	•	T	1	4	
2	U	1	100	4	70			s	0	1	S) 2	T	. 0	1	T	0	4	
3	D	0	0	1							,			•	•				Included with above
4	U	2	2	0	350	I		S	0	1	S) 2	2 1	0	1	T	0	4	
5	D	0	0	1							,	,							Included with above
6	U	2	3	9	350	1		S	0	-	S) 2	I	0	1	T	0	4	
7	D	0	0	1					_	1	_	_		_					Included with above
8	U	0	5	2	200	T		S	0	1	s c) 2	T	0	1	T	0	4	
9	U	2	2	6	300	T		S	0	1 :	s c) 2	T	0	1	T	0	4	
10	U	1	5	9	350	T		S	0	1 1	s c	2	T	0	1	T	0	4	
11	D	0	0	1					_										Included with above
12	Ū	0	6	1	175	T		S		1 8	5 0		T	0	1		0	4	
13	D	0	0	1			-						L						Included with above
14	Ū	2	1	0	300	T		S		1 8	3 0	2	T	0	1	T	0	4	
15	U	1	0	7	90	T		S			3 0					T	0	4	
16	U	0	8	8	90	Т		S			3 0			0	1		0		
17	D	0	0	1	2500	T		S	0 1	1 5	3 0	2	T	0	1	T	0	4	
18	D	0	0	2	2500	T		S	0 1	1 8	3 0	2	T	0	1	T	0	4	
19	D	0	0	3	250	T		S	0 1	1 5	3 0	2	T	0	1	T	0	4	
20	D	0	0	7	800	T		S) 1	1 8	3 0	2	T	0	1	T	0	4	
	D	0	0	8	2000	T		S) 1	1 5	0	2	T	0	1	T	0	4	
	D	0	0	6	400	T		S) 1	S	0	2	T	0	1	T	0	4	
	D	0	0	9	400	T		S) 1	S	0	2	T	0	1	T	0	4	
	D	0	0	4	400	T		S) 1	S	0	2	T	0	1	T	0	4	
25	4	9	2	9	1000	r		SC) 1	S	0	2	T	0	1	T	0	4	
PA Fo	U	ä	4	1	90	7		s c			0		7	0		T'	0		
PA Fo		101	0-3	16-8	0)		To the								_				CONTINUE ON REVERSE

PAGE 3 R OF 5

CONTINUE ON REVERSE

ב שנישב ארצות במשב ביותר עם במותר או בשבות ביותר ביות	ר שיי לי יופרי שיי רי פינד ע	स.च्या	F
EPA LO HIJMEER lenter mm Jige 1,	<u> </u>	FIGO OFFICIAL USE	SHE'S THE FACT PARTICION WILL SHE'SLE'S
W. C.D.) A F. P. C. D. C. L.	, M	() (; P	DUP
A. EPA	CUNIT		D. PROCESSES
MAZARO B. ESTIMATED ANNUA OUANTITY OF WASTE	(enter t. r	rencess codes fenters	2. PROCESS DESCRIPTION life code w not entered in Dilli
1 11 0 4 4 30	1111.	021711794	
2 0 2 2 7 90	T SOIS	02 701 704	
3 17 1 1 8 90	T S 0 1 S	02 T 0 1 T 0 4	Page Waller of the St
4 0 1 0 2 90		0 2 T 0 1 T 0 4	
5 0 9 6 90	T S01S0	02 T 0 1 T 0 4	
6 0 1 1 3 90	T S01S0	0 2 T 0 1 T 0 4	
7 F 0 0 4 2500		2 T O 1 T O 4	
8 F 0 0 6 90.		2 T O 1 T O 4	
9 F 0 1 9 90		2 T O 1 T O 4	
10 F 0 0 7 90	111,111		To the plant specific
11 F 0 0 8 90	T S01S0	1 1 1 1 1 1	
12 F 0 0 9 90			
13 F 0 1 0 90		2 T O 1 T O 4	
14 F 0 1 2 90	11111	2 T O 1 T O 4	
15 K 0 0 2 90		2 T O 1 T O 4	
6 K 0 0 3 90		2 T O 1 T O 4	
7 K 0 0 4 90	T S 0 1 S 0	1,,,,,	
8 K 0 0 5 90	T S 0 1 S 0	11111	
9 K O O 6 90	111111	11111	
0 K 0 0 7 90	1111	11111	
1 K 0 0 8 90		2 T O 1 T O 4	
2 7 0 0 0 0 0 0		2 T O 1 T O 4	
3 7 0 0 0	11,,1,,	2 T O 1 T O 4	
l v a a v	T S 0 1 S 0 3	1111	
	T S 0 1 S 0 2	1111	
K 0 9 4 90	T S 0 1 S 0 2	1111	
Form 3510-3 (6-80)	T S 0 1 S 0 2	T 0 1 T 0 4	

PAGE 3 C OF 5

EPA Form 35103 16-201

P 0 6 4

90

26

PAGE 3 TOF 5 tester "1" "2" "

S 0 1 S 0 2 T 0 1

S 0 1 S 0 2 T 0 1 T 0 4

T 0 4

CONTINUE ON REVERSE


Continued from page 2.
NOTE. Photocopy this page before completing if you have more than 25 wastes to list

	, , , , , , , , , , , , , , , , , , , ,	`	1		-044 ADD-0449 OWR 1/9 . 28-29C004
·		1/	1	W	DUP 12 DUP
	V. DESCRIPTION OF HAZARDOUS WAS	TES	Cont	nuedl	
	A. EPA HAZARD. B. ESTIMATED ANNUA WASTENO: QUANTITY OF WASTE	100	UNIT MEA- URE enter rode)		1. PROCESS CODES (If a code is not entered in D(1))
	1 P0174. 90	"	11	1	10: 17 - 10 17 - 10 17 - 10
-			T	150	1 S O 2 T O 1 T O 1
H	P 0 8 9 90	-	T	S ₀	1 S O 2 T O 1 T O 4
L	P 0 9 4 90		T	S O	1 S O 2 T O 1 T O 4
-	P 0 4 3 90		T	S O	1 S O 2 T O 1 T O 4
1	5 P 0 4 0 90		T	S O	1 S O 2 T O 1 T O 4
1	P 0 9 7 90		T	S O	1 S O 2 T O 1 T O 4
1	P 0 9 8 90		T	S 0	
8	P 0 7 5 90		T	S 0	
9	P 1 1 1 3 90	П	T	S 0	
10	P 1 0 4 90		T :	S 0	
1	P 1 0 6 90		T	S 0	1 S O 2 T O 1 T O 4
1:	P 1 0 8 90		r	S 0	1 S O 2 T O 1 T O 4
13	P 1 1 0 90		r	S 0	1802 T 0 1 T 0 4
14	P 1 2 3 90		T	S 0	1 S O 2 T O 1 T O 4
15	! P: 1 2 0: 90		r	8.0	1802101104
	P 1 2 1 90		T	S O	1802 TO 1 TO 4
17	U 0 0 7 . 90	1		3 0	1 5 0 2 T 0 1 T 0 4
18	11 0 0 8 90			3 0	1 S O 2 T O 1 T O 4
19	U 0 0 9 90				1 S O 2 T O 1 T O 4
20	U 0 1 2 90	1		3 0	1 8 0 2 T 01 T 0 4
21	U 0 7 0 90	1		3 0	1 S O 2 T O 1 T O 4
22	U 0 7 1 90	r		3 0	1 S O 2T O 1 T O 4
23	11 0 7 2 90	I		3.0	1 S O 2T O 1 T O 4!
24	U 1 5 9 90	r		3 0	1 S 0 2T 0 1 T 0 4
<u></u>	U 21 1 90	T	1	3 0	1 S O 2T O 1 T O 4
-	U 0 3 7 90	Ţ	S	0 1	1 S O 2 T O 1 T O 4
EFA	orm 3510-3 (6-80)				E 3 E OF 5

Continued from page NOTE Photocopy in	2. In page before completing if you	heve more	tien.	שניים מי ניין ניין איניים פי	5
	sem 'enter from page !)	111	S. C.	POR OFFICIAL USE	Form Approved CMB No '58-580004
ILITIDIO 8		1 1	w	DUP	12 DUP
PROPERTY OF THE PROPERTY OF THE PARTY OF THE	N OF HAZARDOUS WAST		uedl	一般的情報報告報告的計算	the state of the s
ZO WASTENOI	8. ESTIMATED ANNUAL QUANTITY OF WASTE	C.UNIT OFMEA- SURE (enter code)		1. PROCESS CODES (enter)	0. PROCESSES 1. PROCESS DESCRIPTION (If a code u not entered in D(1))
1 0048	90		S 0	1 S O 2 T O 1 T O 4	
2 0 0 5 5	90	T	5 0	1 S 0 2 T 0 1 T 0 4	
3 0240!	90	T	5,0	1802701704	
4 U 0 7 8	90	T	3.0	1 S O 2 T O 1 T O 4	
6 1 1 9	90	T 18	3 0	1 S O 2 T O 1 T O 4	
7	90	TS	3 0	1 S O 2 T O 1 T O 4	
8	90	T	50	1 S O 2 T O 1 T O 4	
9 0 9 2	90	TS	11	1 1 1 1 1 1 1 1	
10 0 0 1	90	TS	0	1 S O 2T O 1 T O 4	
II U 1 1 2	90 .	T ·· S		1 S O 2T O 1 T O 4	
12 0 1 1 7	90	TS		1 S O 2T O 1 T O 4	
13 0 1 2 2	90		0	1 S O 2T O 1 T O 4	
4 0123	90	TS	0	S 0 2T 0 1 T 0 4	
5 U 2 1 3	90		0	S 0 2T 0 1 T 0 4	,
6 0125	90	TS	0	S 0 2T 0 1 T 0 4	全国企业的
7 0 1 2 7	. 90	TS	0 1	S 0 2 T 01 T 0 4	HALLY THE LOCK
3 11 2 8	90	T S	0 1	S 0 2 T 01 T 0 4	
Л 1 3 3	90	TS	0 1	S 0 2 T 0 1 T 0 4	
U 1 3 4	90	TSO		S 0 2 T 0 1 T 0 4	
10111410	90	TSO) 1	S 0 2 T 0 1 T 0 4	
11111111	90	TISO) 1	S 0 2 T 0 1 T 0 4	
11111	90	TSO	1	S 0 2 T 0 1 T 0 4	A STATE OF THE STA
1147		TSO	1	S 0 2 T 0 1 T 0 4	
U1151	The state of the s	T SO	1	S 0 2 T 0 1 T 0 4 S 0 2 T 0 1 T 0 4	
Form 3510-3 (6-80)		T S O	79 1	0 0 2 1 0 11 1 0 4	

PAGE 3 .1 OF 5

tinued from page 2. TE Photocopy this dage defore completing if you have more than 26 wastes to list Form Approved OMB No. 158-580004 EPA 1.0. NUMBER (enter from page 1) FOR OFFICIAL USE ONLY w WILLD191815131419196411 DUP DUP IV. DESCRIPTION OF HAZARDOUS WASTES (continued) - Man - 1 1 2 2 M HAZARO.
ZO WASTENO C. UNIT OF MEA-SURE Jenter code) B. ESTIMATED ANNUAL QUANTITY OF WASTE D. PROCESSES 1. PROCESS CODES 11 a code u not entered in 2(1) 14 17 - 10 17 - 10 17 - 10 17 - 19 1121417 S 0 1 S 0 2 T 0 1 T 0 4 1 T 90 S 0 1 S 0 2 T 0 1 T 0 4 6 90 T 3 90 S 0 1 S 0 2 T 0 1 T 0 4 90 S 0 1 1 S 0 2 T 0 1 T 0 4 5 1 6 U 90 S 0 1 S 0 2 T 0 1 T 0 4 6 19 90 S 0 1 S 0 2 T 0 1 T 0 4 18 8 U 1 90 S 0 1 S 0 2 T 0 1 T 0 4 11 90 90 T S 0 1 S 0 2 T 0 1 T 0 4 9 ::. 9 90 S 0 1 S 0 2 T 0 1 T 0 4 T 10 0 90 T S 0 1 S 0 2 T 0 1 T 0 4 11 90 S01802T01T04 12 90 S 0 1 S 0 2 T 0 1 T 0 4 13 0 9 90 T S 0 1 S 0 2T 0 1 T 0 4 90 S 0 1 S 0 2T 0 1 T 0 4 15 2 U: 2 90 T S 0 1 S 0 2T 0 1 T 0 4 16 U. 2 2 8 S 0 1 S 0 2T 0 1 T 0 4 90 T 90 S 0 1 S 0 2T 0 1 T 0 4 18 19 20 21 25 26 42



43

AUG 08 1985

BART A LOG: A179

NAME : PETROCHEM

CITY : LEMONT

TYPE (LN, NW, PO 50, 50, FE, OT) :

DATE REC'D : 88/01/21

CRIPARTA:

PROCESS: AMOUNT 1:
PROCESS: AMOUNT 2:
PROCESS: AMOUNT 3:
PROCESS: AMOUNT 4:
PROCESS: AMOUNT 5:
PROCESS: AMOUNT 6:

COMMENTS :

SITE NO. : 0311620007

USEPA ILD : ILD085349264

COUNTY : DOCK

REVIEWER : MAS

DATE MAILED: 86/03/14 PRP/DEN/FE: APP

NOTIFY FOB:

UNIT 1: ADD/DEL 1:
LNIT 8: ADD/DEL 3:
UNIT 3: ADD/DEL 3:
UNIT 4: ADD/DEL 4:
UNIT 5: ADD/DEL 5:
LNIT 6: ADD/DEL 6:



217/782-6762

Refer to:

0311620007 -- Cook Petrochem Services

Permit File Log 1987-263

March 10, 1988

Petrochem Services, Inc. Attn: George A. Smith P.O. Box 337 Lemont, IL 60439

Gentlemen:

This letter is to inform you that the Agency has revised your Operating Permit 1983-5-OP to include the following modifications:

- To allow fuel blending in Tanks ST-2, ST-3 and ST-5.
- B. To permit wastes with a vapor greater than 1.5 psia or with a flash point less than 100F to be stored or treated in Tanks OS-2, ST-1, ST-4 and ST-6.
- C. To increase the type of waste streams which can be accepted.
- D. To expand the drum crushing operation to cover empty drums received from off site.
- E. To allow containerized storage in van trailers.
- To allow additional consumer products to be accepted for the shredder unit.
- The clarification of site operations as outlined in your letter of February 18, 1988.

Additional modification requests to your operating permit were not granted because you have failed to provide proof that granting this permit would not result in violations of the Ill. Environmental Protection Act. Section 39(a) of the Illinois Environmental Protection Act (Ill. Rev. Stat., 1979, Ch. 111 1/2, par. 1039(a)) requires the Agency to provide the applicant with specific reasons for the denial of permit. The following reason(s) are given:

In regards to dropping the list of solvents suitable for fuel blending or off-site incineration it was not the intent of the Agency to replace the supplemental waste stream system with the generic permit nor to allow the permittee to decide what wastes are suitable for fuel blending or off-site incineration without first consulting the Agency through the above mechanisms. Additionally, it was not felt that all wastes approved to be received were suitable for fuel blending due to their low BTU valve, high flash point or classification as nonflammable. If these materials are to be reconsidered by the Agency at a later date the following information



Page 2

- justification why the material is better handled through fuel 1. blending than off-site incineration.
- 2. what percentage of chlorine is in the fuel
- a copy of the contract which allows chlorine at these levels in the
- 4. how long are these type of wastes stored before they are blended
- 5. do the burner of these wastes have an air permit which allows this composition of fuel to be burned.

Additionally your revised closure plan dated February 26, 1985 and your revised part A dated February 25, 1988 have been reviewed and approved.

Should you wish to reapply or have any questions regarding this application, please contact Mark A. Schollenberger at 217/782-9799.

Very truly yours,

Lawrence W. Eastep, P.E., Manager Permit Section Division of Land Pollution Control

LWE:MS:mab/0207j/sp

Enclosures

cc: Northern Region Division File DAPC - Jim Cobb Compliance Monitoring Jeanetter Virgillo - RUI, Inc.

Document 002



Illinois Environmental Protection Agency 2200 Churchill Road, Springfield, IL 62706

217/782-6762

Refer to:

0311620007 -- Cook County

Petrochem Services, Inc.

ILD085349264

Permit No. 1983-5-0P

Log No. 1987-263 (1987-15, 1986-164 1986-39)

July 17, 1987 Revised April 15, 1987 Revised March 10, 1988

Petrochem Services, Inc. Attention: George E. Smith P.O. Box 337 Lemont, IL 60439

Gentlemen:

Permit is hereby granted to the above facility to operate a waste site consisting of 17 acres in the N 1/2 of Section 21, Township 37 N. Range 11E, 3rd P.M. (as more fully described in the original application) to store, treat and/or reclaim waste, surplus or off-specification materials.

Final plans, specifications, application and supporting documents as submitted and approved shall constitute part of this permit and are identified on the records of the Illinois Environmental Protection Agency by the permit number(s) and log number(s) designated in the heading above.

This permit is issued subject to the standard conditions attached hereto and incorporated herein by reference and further subject to the following special conditions:

This permit allows Petrochem to operate the following units:

a.

Tank Designation	Volume Per Tank (Gals.)	Usage
ST-1	7,686	Waste/Product Storage and Fuel Blending
ST-2	10,380	Waste/Product Storage and Fuel Blending
ST-3	11,177	Waste/Product Storage and Fuel Blending
ST-4	10,981	Waste/Product Storage and Fuel Blending



Illinois Environmental Protection Agency

Page 2	4	
--------	---	--

The second second		
ST-5	7,686	Waste/Product Storage and Fuel Blending
ST-6	7,686	Waste/Product Storage and Fuel Bending
0S-1	62,375	Waste/Product Oil Storage
0S-2	62,375	Waste/Product Oil Storage and Fuel Bending
HT-1	19,828	Heat/Treatment and Waste/Product Oil Storage
HT-2	19,828	Heat/Treatment and Waste/Product Oil Storage
HT-3	19,828	Heat/Treatment and Waste/Product Oil Storage
HT-4	19,828	Heat/Treatment and Waste/Product 0il Storage
CB-1	21,401	Oily Waste Treatment/Holding Tank
CB-2	21,401	Oily Waste Treatment/Holding Tank
CB-3	21,401	Separated Water Treatment Tank
CB-4	21,401	Sludge/Water Holding Tank
VR-1	5,875	Waste Storage
VR-2	5,287	Waste Storage
VR-3	5,287	Waste Storage
WS-1	28,481	Water Storage Tanks
WS-2	28,481	Water Storage Tanks
LS-1	10,528	Lime Slurry Storage Tank
PT-1	550	Process Liquid Waste Storage from Shedding Unit ONLY
PT-2	550	Process Liquid Waste Storage from Shedding Unit ONLY



Page 3

PT-3	550	Process Liquid Waste Storage from Shedding Unit ONLY
PT-4	550	Process Liquid Waste Storage from Shedding Unit ONLY
PT-5	550	Process Liquid Waste Storage from Shedding Unit ONLY

Container Storage Areas

Unit Designation	<u>Volume</u>	Usage
Drum Storage Area 1	600 drums	Waste Drum Storage
Drum Storage Area 2	160 drums/ 55 gal drum	Waste Drum Storage for the Shredding System ONLY
Storage roll-off boxes	(1) 15 C.Y. (1) 20 C.Y.	Solid Waste Storage for landfill disposal
Containerized Storage in van trailers	(10) 80 drums/ 55 gal drum	Waste Drum Storage

Processing Units

- Plate and frame filter press unit
- 2. Boiler with Fuel Storage Tanks
- 3. Heat Exchangers (2)
- Shed-pax AZ-15 shredder with conveyors, fire suppression, 4. exhaust and liquid collection systems
- All corresponding sumps, pumps, piping controls, filters, 5. loading and unloading areas and appurtenances.
- Waste, surplus and off-specification materials for storage, treatment, recycling, blending into fuels, blending for off-site incineration or shredding for volume reduction shall be limited to the following:
 - a. 0ils
 - 1. engine lube oils
 - 2. transmission fluids
 - 3. hydraulic oils



Page 4

- 4. insulating fluids and coolant oils
- metal working fluids (cutting, grinding, machine, rolling, 5. stamping and quenching oils)
- 6. turbine oils
- 7. gear oils
- 8. greases
- 9. distillate and residual fuel oils
- 10. tallows
- 11. vegetable oils
- 12. paraffins
- 13: mineral oils
- 14. petroleum refining intermediates (cycle, decant and slop oils)
- 15. asphalt
- 16. sulfonate oil
- 17. oil/water separator wastes
- 18. bilge oil wastes
- 19. oily washwaters and bottoms of the above from barge and tank cleaning operations
- 20. spill clean-up residues of the above
- 21: pipeline interfaces and transmixes of the above

b. Solvents*

Non-halogenated Aliphatics:

- mineral spirits
- 2. napthas
- 3. paraffin solvents
- 4. plasticizers
- 5. styrene
- 6. jet fuel
- 7.
- gasoline
- 8. heptane
- 9. cyclohexane
- 10. hexane
- 11. kerosene
- 12: lacquer thinner
- 13. stoddard's solvent
- 14. turpentine
- 15. isoprene
- 16. pentane
- 17. hexene's
- 18. isopentane
- 19: methyl cyclohexane
- 20. isoctane

Non-halogenated Aromatics

- xylene
- 2. benzene
- 3. toluene

Halogentated Aliphatics:

- 1. tetrachloroethylene
- 2. trichloroethylene
- 3. methylene chloride
- 4. 1,1,1-trichloroethane
- 5. carbon tetrachloride
- 6. chlorinated fluorocarbons
- 7. chlorobenzene
- 8. 1,1,2-trichloro-
 - 1,2,2-trifluoroethane
- 9. orthodichlorobenzene
- 10. trichlorofluoromethane
- 11: dichl orobenzene

Esters

50

- 1. ethyl acetate
- 2. vinyl acetate
- 3. dioctyl phthalate

Page 5

- 4. cumene
- 5. cresols
- 6. cresylic acid
- 7. nitrobenzene
- 8. ethyl benzene

- diethyl phthalate
- 5. methyl acetate
- 6. isobutyl acetate
- 7. isopropyl acetate
- 8. isoamyl acetate
- 9. amyl acetate
- 10. ethyl methyl acrylate
- 11. ethyl acrylate

Alcohols:

- 1. ethanol
- 2. ethylene glycol
- 3. butanol
- 4.. isobutyl alcohol
- 5. methano1
- 6. isoamyl alcohol
- 7. tert amyl alcohol
- 8. cyclohexanol
- 9. diacetone alcohol
- 10. 2-ethy1-1-butanol
- 11. 2-ethy1-1-hexanol
- 12. ethyl butanol
- 13. isopropyl alcohol
- 2-methyl 2-butanol 14.
- 15. propanol
- 16. 2-methyl-1-propanol
- 17. n-octanol

Ketones:

- 1. acetone
- 2. MEK
- 3. MIBK
- 4. diacetone alcohols
- 5. acetophenone
- diisobutyl ketones 6.

*This includes still bottoms from recovery, tank bottoms, washwaters and spill clean-up residues of the above.

- Hazardous waste from specific sources
 - 1. DAF float - KO48
 - 2. slop oil emulsion solids - KO49
 - heat exchange bundle cleaning sludge KO50 3.
 - 4. API separator (leaded) - KO51
 - 5. tank bottoms (leaded) - K052
 - ink formulation waste KO86 6.
- Corrosive Waste
 - 1. sodium hyrdoxide
 - 2. potassium hydroxide
 - 3. wastewaters and bottoms containing NaCH and KOH from tank or barge cleaning operations
 - 4. sulfuric acid
 - 5. phosphoric acid
 - 6. wastewaters and bottoms from sulfuric and phosphoric acid storage tank cleaning operations



Page 6

- Aerosol and non-aerosol products for the shedder system only:
 - 1. soaps and detergents
 - 2. alkaline cleaners
 - 3. air fresheners
 - 4. health and beauty aids
 - 5. petroleum products
 - 6. food products
 - 7. paints and related products
 - 8. construction products, i.e.: adhesives, cements, insulation
- Additional solvents available only for storage, recycling, and off-site incineration.
 - 1. creosote
 - 2. 1-3 butylene glycol
 - 3. propylene glycol
 - 4. chloroform
 - 5. perchloroethylene
 - 1,1,2-trichloroethane 6.
 - 7. dimethyl phthalate
 - 8. di-n-butyl phthalate
- This permit also allows for the temporary storage of wastes in containers (of those not identified above) resulting from emergency response spill clean-up for purposes of sampling, analysis and staging for off-site treatment, disposal, incineration or recovery.
- Treatment, as permitted herein, is limited to:
 - Oil/hydrocarbon treatment system consisting of physical and chemical separation processes (clarification, coagulation, floculation, flotation, decanting, sedimentation, filtration, chemical treatment, and heating) to remove and separate water and solids from the hdyrocarbon phase of wastes, which shall also include the following pre-treatment processes:
 - Reactive waste neutralization for sulfides (maximum allowable concentration at 1000 ppm) in oils and oil/hydrocarbon mixtures using sodium hypochlorite as an oxidizing agent.
 - 2. Reduction of hexavalent chrome contaminated cooling oils (maximum allowable concentration at 1000 ppm) utilizing sodium hydrosulfite.
 - Acid pre-treatment of oil and oil/water emulsions.
 - Acid/base neutralization.



Page 7

- Blending oils/hydrocarbon mixtures into supplementary fuels or for purposes of off-site incineration.
- Solids conditioning with lime (of wastes generated from other on-site d. processes).
- Solids dewatering (of waste generated from other on-site processes) e. using a plate and frame filter press.
- 5. Any wastes or materials with a vapor pressure greater than 1.5 psia or with a flash point less than 100F shall be stored or treated in the vapor controlled storage/treatment system consisting of tanks labeled OS-2, ST-1 ST-2, ST-3, ST-4, ST-5, ST-6, HT-4, CB-2, CB-3 and CB-4.
- Reactive sulfide neturalization and ehxavalent chrome reduction shall be conducted only in the tank designated as VR-1.
- 7. This facility cannot accept any wastes containing polychlorinated biphenols (PCBs) at a concentration greater than 10 ppm.
- 8. Each waste stream received for storage or treatment shall be analyzed and processed in accordance with the procedures described in the application to assure that:
 - The waste stream is properly classified, and
 - None of the followign wastes are accepted for treatment:
 - Reactive wastes (other than sulfide reactive oil mixtures with a sulfide content of 1000 ppm).
 - Poisonous wastes as defined by 49 CFR, Part 173, Subpart H, Section 173. 326 and Section 173.343.
 - Any waste containing material regulated by the Federal Insecticide, Fungicide and Rodenticide Act, as amended.
- 9. This 3 Carbon Absorber Control devices on ST-1, St-4, St-6 shall be inspected weekly for deterioration and/or leakage.
- 10. This facility shall be operated in accordance with this Agency's Division of Air Pollution Control Permits.
- 11. All loading/unloading of special wastes shall be accomplished over spill containment devices.
- 12. Drums of special waste shall be stacked a maximum of two high on pallets.



. . . .

Page 8

13. All wastes received for fuel blending into the used oil program shall be analyzed for total halogen. To date, the only USEPA approved teste method for total halogens is ASTM method D808-81 (i.e. oxygen bomb followed by titrimetric halogen determination). Petrochem shall use the following rebuttal method for determining halogentated solvents in wastes received for blending into fuel to be marketed as used oil:

Used oil or wastes containing more than 1,000 ppm of total halogens is presumed to be hazardous waste unless adequately rebutted by the generators. It is important to note that simply showing that the amount of chlorinated solvents in the oil is less than 1,000 ppm by GC/MS analysis (ie. SW-846 method 8240) is not an adequate rebuttal to the presumption. For example, if the oil has a total halogen concentration of 3,000 ppm (by ASTM method 808), and the GC/MS analysis indicates 800 ppm of trichloroethylene, the presumption has not been adequately rebutted. The generator must still (1) identify the source(s) of all of the 3000 ppm chlorine and (2) prove that the 800 ppm of trichloroethylene is not the result of mixing the oil with a listed hazardous waste. At a minimum, the rebuttal shall include (1) the concnetrations of halogenated solvents as determined by GC/MS Test Methods (i.e. SW-846 method 8240), (2) if available, material safety data sheets for the waste. The MSDS's must include % chlorine in each waste and the source (i.e., chlorinated paraffins) (3) process descriptions of the operations generating the waste. The description should identify the operations (including those which use solvents) raw materials, and products which may introduce chlorine into the process and (4) the generator certification form. copy of the rebuttals shall be submitted with the renewal application for generic permits.

- 14. QC Test 6 that was submitted to the Agency on January 22, 1987 shall replace the QC Test 6 for Group I Waste Quality Control Test 6 previously submitted and approved.
- 15. Special waste received at the site for stroage and treatment/recovery shall be transported to the facility utilizing the Agency's supplemental waste stream permit or generic permit system and manifest system.
- 16. Special wastes generated at the site for disposal, storage, incineration or further treatment elsewhere shall be transported to the receiving facility utilizing the Agency's supplemental waste stream permit system and manifest system.
- 17. This permit is subject to review and modification by the Agency, as deemed necessary to fulfill the intent and purpose of the Environmental Protection Act, and all applicable environmental rules and regulations.
- 18. This permit is issued with the expressed understanding that no process discharge to waters of the State or to a sanitary sewer will occur from these facilities. If such discharge occurs, additional or alternate facilities shall be provided. The construction of such additional or



Page 9

- 19. Any modification to the facility shall be the subject of an application for supplemental permit for site modification submitted to this Agency.
- 20. Permittee shall notify the Agency of any changes from the information submitted to the Agency in its application for a development and operating permit for this site. Permittee shall notify the Agency of any changes in the names or addresses of both beneficial and legal changes in the names or addresses of both beneficial and legal titleholders to the herein-permitted site. Such notification shall be made in writing within fifteen (15) days of such change and shall include the name or names of any parties in interest and the address of their place or abode; or, if a corporation, the name and address of its registered agent.
- 21. Drums received from off site for crushing which contained hazardous waste must be empty as defined in Section 721.107 of Subtitle G. when received.

Very truly yours.

Lawrence W. Eastep, P.E., Manager Permit Section Division of Land Pollution Control

LWE:MS:mab/207j/sp

Enclosures

cc: Northern Region Compliance Monitoring Division File Jeanette Virgillio, RUI, Inc. DAPC - Jim Cobb



217/782-6762

Refer to:

0311620007 -- Cook Petrochem Services

Permit File

Log No's 1987-240, 1987-241

March 10, 1988

Petrochem Services, Inc. Attn: George A. Smith P.O. Box 337 Lemont, IL 60439

Gentlemen:

This letter is to inform you that the Agency has revised your Generic Permit 1986-116-SP to include the following waste stream modifications:

- to replace waste stream components total water and total solids with the component bottom sediment and water for generic permits 000105 through 000118, 000172, 090010 and 090011.
- to increase the limit for the componenet, total halogenated solvent to 10% for generic permits 000112 and 000113.
- to increase the limits for the components, arsenic, cadmium, lead and chromium to 1% for generic permits 000105, 000106, 000108, 000110, 000111, 000114, 000115, 000116, 000117, 000172 and 090011.
- D. to add D001, D002, D003, D004 and D006 to USEPA Hax #'s for generic permits, 000106, 000111, 000114, 000115 and 000117.
- to add U057, U112, U107, U088, U031, U140, U159, U161, K086, D001, D002, D003, D004, D006, D007, and D008 to USEPA Hax #'s for generic permit 000108.
- F. to add D001, D002, D003, D004, D006, D007, D008 and F004 to USEPA Hax #'s for generic permit 000116.
- G. to add D002, D003, D004, D006, D007 and D008 to USEPA Hax #'s and remove the component chloride and increase to component total halogentated solvents to 10% for generic permit 000172.
- to add U057, U112, U107, U088, U031, U140, U159, U161, D001, D003, D004, D006, D007 and D008 to USEPA Haz #'s for generic permit 090011.
- to increase the solids component to 100% and water component to 95% and correct the treatment method for generic permits 000119 and 000120.
- to add silver as a component of generic permit 000174 and delete the componenet, total halogenated solvent. 56



Page 2

- to add additional specific waste types for recovery.
- to grant a generic permit for RCRA empty drums.

Additional modification requests to your permit were not granted because you have failed to provide proof that granting this permit would not result in violations of the Illinois Environmental Protection Act (Ill. Rev. Stat., 1979, Ch. 111 1/2, par. 1039(a)) requires the Agency to provide the applicant with specific reasons for the denial of permit. The following reason(s) are given:

In regards to creating a generic permit titled "used oil" and one title "waste, off-spec and surplus oil" as opposed to the one permit currently issued, the Agency does not see the need for this in running the generic permit program.

Should you wish to reapply or have any questions regarding this application, please contact Mark A. Schollenberger at 217/782-9799.

Very truly yours,

Lawrence W. Eastep, P.E., Manager Permit Section Division of Land Pollution Control

LWE:MS:mab/207j/sp

Enclosures

cc: Northern Region Division File DAPC - Jim Cobb Compliance Monitoring Jeanett Virgillio



217/782-6762

Refer to: 0311620007 -- Cook County

Petrochem Services, Inc.

ILD085349264

Permit No. 1983-5-OP (Revised 7/17/86) Supplemental Permit No. 1986-116-SP

Log No's 1987-240 & 1987-241 (1987-154, 1987-016, 1986-116)

Expiration Date: July 17, 1989

July 17, 1986 Revised August 28, 1987 Revised March 10, 1988

Petrochem Services, Inc. Attn: George A. Smith Post Office Box 337 Lemont, Illinois 60439

Gentlemen:

Supplemental Permit Number 1986-116-SP is hereby issued to the above facility, to accept for storage and/or pretreatment for purposes of recovery, recycling, blending into supplemental fuels or blending for off-site incineration and aerosol/non-aerosol product shredding the following wastes, surplus or off-specification materials from any IEPA registered generator on a generic basis:

A. For Recovery *

- Non-halogenated aliphatics including mineral spirits, naphthas, paraffin solvents, plasticizers, styrene, jet fuel, gasoline, heptane, cyclohexane (U057), hexane, kerosene, lacquer thinner, paint thinner, stoddard solvents, turpentine, isoprene, pentane, hexene, isooctane, isopentane and methyl cyclohexane (see attached Waste Stream Permit Nos. 000112 and 000117);
- Non-halogenated aromatics including xylene (F003, U239), benzene (U019), toluene (F003, U220) cumene (U055), cresol (F004, cresylic acid (F004) creosote (U051), ethylbenzene (F003) and nitrobenzene (F004) (see attached Waste Stream Permit No. 000116);
- 3. Alcohols including ethanol, ethylene glycol, butanol (UO31), isobutyl alcohol (U140) isoamyl alcohol, tert-amyl alcohol, cylcohexanol, diacetone alcohol, 2 ethyl-1-butanol, 2-ethyl-1-hexanol, ethyl butanol, ispropyl alcohol 1,3 butylene glycol, 2-methyl-2-butanol, propanol, 2-methyl-1-propanol, propylene glycol, n-octanol and methanol (U154) (see Waste Stream Permit No. 000113 and 000115);

Page 2

- Ketones including acetone (F003, U002), MEK (F003, U159) cyclohexane, isphorene, acetophenone, diacetone alcohols, diisobutyl ketones and MIBK (F003, U161) (see attached Waste Stream Permit No. 000114);
- Halogentated aliphatics (F001, F002) including tetrachloroethylene, trichloroethylene, methylene chloride, 1,1,1-trichloroethane, carbon tetrachloride, chlorobenzne, 1,1,2-trichloro-1,2,2-trifluoroethane, orthodichlorobenzene chloroform (UO44), perchloroethylene, dichlorobenzene, 112 trichloroethane (U227) and trichlorofluoromethane (see attached Generic Waste Stream Permit No. 000118);
- Esters including ethyl acetate (F003), vinyl acetate (D001), dioctyl phthalate (U107) methyl acetate, isobutyl acetate, isopropylacetate, isoamyl acetate, amyl acetate, ethyl methacrylate (Ul18), dimethyl phthalate (U102), di-n-butyl phthalate (U069), ethyl acrylate (U113) and diethyl phthalate (U088). (See Waste Stream Permit 000172).
- Corrosive waste (DOO2). (See attached Waste Stream Permit NO. 7. 000119).
- Non-hazardous used, waste, off-spec and surplus oils. (See attached 8. Waste Stream Permit 000110).
- 9. Hazardous used, waste, off-spec and surplus oils (KO48, KO49, KO50, KO51, KO52, D005, D006, D007, D008, D009, D010, D011). (See attached Waste Stream Permit 000111).

The oils* permitted for acceptance under Generic Permits 0001110 and 000111 arelimited to the following:

engine lube oils transmission fluids hydraulic oils insulating fluids and coolant oils turbine oils gear oils greases distillate and residual fuel oils tallows vegetable oils parrafins

asphalts sulfonate oils oil/water separator wastes

bildge oil wastes Petroleum refining intermediates: (cycle, decant and slop oils) metal working fluids: (cutting, grinding, maching, rolling, stamping and quenching) mineral oils

Page 3

listed hazardous petroleum refinery wastes:

1. DAF float -- KO48

2. slop oil emulsion solids -- KO49

3. heat exchange bundle cleaning sludge -- KO50

API separator sludge -- KO51

5. tank bottoms (leaded -- KO52)

This includes still bottoms, tank bottoms, barge bottoms, washwaters and spill clean-up residues.

For Blending into Supplemental Fuels

- Non-hazardous used, waste, off-spec and surplus oils. (See attached 1. Waste Stream Permit 000105).
- Hazardous used, waste, off-spec and surplus oils (KO48 thru KO52, 2. D005, D006, D007, D008, D009, D010, D011). (See attached Waste Stream Permit 000106).

The oils* permitted for acceptance under Generic Permits 000105 and 000106 are limited to the following:

engine lube oils transmission fluids hydraulic oils insulating fluids and coolant oils turbine oils gear oils greases distillate and residual fuel oils tallows vegetable oils parrafins mineral oils

asphalts sulfonate oils oil/water separator wastes

bildge oil wastes Petroleum refining intermediates: (cycle, decant and slop oils) metal working fluids: (cutting, grinding, maching, rolling, stamping and quenching) Listed hazardous petroleum refinery wastes:

1) DAF float -- KO48

2) slop oil emulsion solids -- KO49

heat exhange bundle cleaning sludge -- KO50

4) API separator sludge -- KO51

5) tank bottoms (leaded) -- K052



Page 4

Non-halogenated solvents and liquids ** including the following: 3. (see attached Waste Stream Permits 000107 and 000108).

mineral spirits napthas paraffin solvents plasticizers styrene jet fuel gasoline heptane hexane cresols nitrobenzene cresylic acid vinyl acetate ethyl acetate diethyl phthalate dioctyl phthalate cyclohexane benzene cumene xylene ethylene glycol toluene ethano1 methanol butanol isobutyl alcohol MIBK acetone MEK Kerosene lacquer thinner paint thinner stoddard's solvent turpentine isoprene pentane hexene isooctane isopentane methylcyclohexane ethyl benzene isoamyl alcohol tert-amyl alcohol diacetone alcohol cyclohexanol 2 ethyl-1-butanol 2 ethyl-1-hexanol ethyl butanol 2 methyl 2-butanol propanol isopropyl alcohol 2 methyl 1-propanol N-octanol cyclohexane isophorene acetophenone diisobutyl ketones methyl acetate isobutyl acetate isopropylacetate isoamyl acetate amyl acetate ethyl methacrylate ethyl acrylate

Washes and sludges from the formulation of ink (KO86)

Halogenated solvents and liquids ** including the following: attached Waste Stream Permit 00109.)

tetrachloroethylene 1,1,1 trichloroethane carbon tetrachloride 1,12-trichloro-1,2,2 trifluoroethane trichlorofluoromethane

trichloroethylene methylene chloride ch1 orobenzene orthodichlorobenze dichlorobenzene

** -- This includes still bottoms, tank bottoms, washwaters and spill clean-up residues.

Bulking/blending for off-site incineration

- 1. Non-halogenated solvents and liquids reference in ITem Al through A4 and A6 above. (See attached Waste Stream Permit 090011.)
- 2. Halogenated solvents and liquids reference in Item A-5 above. (See Waste Stream Permit 090010.)



Page 5

For Treatment

- 1. Corrosive waste for neutralization (DOO2) including sulfuric acid, phosphoric acid, sodium hydroxide and potassium hydroxide. (See attached Waste Stream Permit 000120.)
- 2. Off-specification or scrap commercial products (DOO1) for shredding which shall be limited to the following:
 - Soaps and Detergents a.
 - b. Household Cleaners
 - Health and Beauty Aids C.
 - d. Food Products
 - Paints and related Products e.

f. Air Fresheners

Shop Products (lube & g. penetrating oils, other petroleum base products)

h. Construction Products (adhesives, cements, sealants)

(See attached Waste Stream Permit 000173).

3. Non-hazardous off-specification or scrap commercial products for shredding which shall be limited to the following:

- Soaps and Detergents a.
- Household Cleaners b.
- Health and Beauty Aids C.
- d. Food Products
- Paints and related Products e. (thinners and removers)
- f. Pallets
- Automotive equipment g.
- h. Air Fresheners
- i. Shop Products (lube & penetrating oils, other petroleum base products)

- Construction Products (adhesives, cements, sealants)
- Electronic Equipment and Components
- Small household 1. appliances
- Construction building m. materials and hardware
- Toys n.
- Confidential documents 0. and records
- Other manfuacturer and p. retail appliances and components

(See attached Waste Stream Permit 000174).

E. For Crushing

"RCRA Empty" containers (see attached Waste Stream Permit 000208).

Final plans, specifications, application and supporting documents as submitted and approved shall constitute part of this permit and are identified on the records of the Environmental Protection Agency, Division of Land Pollution Control by the permit number(s) and log number(s) designated in the heading above.



Page 6

The permit is issued subject to the standard conditions attached hereto and incorporated herein by reference, and further subject to the following special conditions:

- An analysis of each waste stream accepted from each generator shall be maintained on file at this site for review by this Agency.
- 2. Special wastes received at this facility for storage, treatment and/or recovery shall be transported to the site under a properly completed manifest.
- 3. The specifications for each supplemental fuel blended on-site, including off-specification used oil fuels and hazardous waste fuels, shall be submitted to the Agency within thirty (30) days after the effective date of this permit. Should the type(s) of fuel blended on-site deviate from the initial submissions, Petrochem shall submit a report to the Agency, identifying the specificaitions for each supplemental fuel blended, prior to shipment off-site.
- Oils contaminated with PCB's (greater than 50 ppm) or Dioxins are not permitted under this generic permit.
- 5. The name and address of any new marketer and/or burner of these blended fuels (includes specification oils, off-specification oils and hazardous waste fuels), along with documentation of certifications that each marketer and/or burner of hazardous wasete fuels or off-specification used oil fuels has so notified USEP and has received a Federal I.D. number, shall be submitted to the Agency prior to shipment off-site to that facility.
- All waste stored at this site for further treatment elsewhere shall be transported to the receiving facility utilizing the Agency's supplemental permit system and manifest system.
- 7. Special wastes generated at the site for disposal, incineration or further treatment elsewhere shall be transported to the receiving facility utilizing the Agency's supplemental permit system and manifest system.
- 8. This facility shall report to the Agency, on quarterly basis, the total quantity from each generator of each of the generic wastes shown in the attachment to this permit that was received for processing. (See New Attached Report Form). In addition, Petrochem shall submit an inventory log for all materials and waste shipped off-site (see enclosed Inventory Report). This information shall be submitted along with the Quarterly Generic Report. The above reports should be sent to:

Compliance Monitoring Section
Division of Land Pollution Control
Illinois Environmental Protection Agency
2200 Churchill Rd
Post Office Roy 19276 63



Page 7

This schedule for submission of these waste receipt reports shall be within 30 days of the end of each quarter (i.e., reports ude by 30th day of January, April, July and October).

Except as modified above, this site shall be operated in accordance with the terms and conditions of Permit No. 1983-5-OP.

Very truly yours,

Lawrence W. Eastep, P.E., Manager Permit Section Division of Land Pollution Control

LWE:MS:mab/0207j/sp

Attachments

cc: Northern Region Division File Compliance Monitoring DAPC -- Jim Cobb Jeanette Virgilio, RUI, Inc.

Document 003

SUMMARY

0311620007

Petrochem Services, Inc. is a service contracting company specializing in oil and chemical industry cleaning, maintenance and emergency spill response. This facility receives hazardous and non-hazardous wastes from off site and blends and treats these wastes to produce hazardous waste fuel, off-specification used oil and on-specification used oil. (Little to no on-spec used oil is generated.) Sources of waste generated off site include cleaning tanker trucks and cleaning off site stationary tanks. This facility also operates an on site barge cleaning operation. They receive hazardous and non-hazardous wastes from IEPA (ERU)/DCI activities (spills, abandoned drums, etc.), Tox-Away (a government-sponsored Indianapolis, IN. project to handle the shipment and disposal of hazardous household wastes) and generators, for temporary storage, which are eventually going off site for incineration.

HAZARDOUS WASTES GENERATED (RESTRICTED)

Hazardous Waste Fuel - D001, F003, F005

- Generated by blending and treating hazardous and non-hazardous waste
- Rate of generation: 45,000 gallons per month
- Shipped off site approximately 3 times per week to Continental Cement (Hanibal, MO.) or Systech (Greencastle, IN.) for use as fuel in cement kilns
- Stored in tanks

APPARENT DEFICIENCY NOTED:

Containers of restricted hazardous waste are not marked to identify the date they entered storage.

1107 15 700

are completed and begin implementing said amendments no later than six months after such changes occur.

Petrochem will review its SPCC at least once every three years and will amend its SPCC Plan to reflect improvements in recognized spill prevention and control technologies which will be implemented to significantly reduce the likelihood of a spill or release.

All amendments to the SPCC plan will reviewed and certified by an independent Registered Professional Ragineer.

Subpart 112.7-Guidelines for the preparation and implementation of a Spill Prevention Control and Countermeasure Plan.

Petrochem Services, Inc. has designed, constructed, maintains and operates its facility in a manner to minimize the possibility of a fire, explosion or any unplanned sudden or non-sudden release of oil, hazardous materials or waste, or the constituents of such materials or waste to the air, soil or surface water which could threaten human health or the environment. See Attachement B, for a list of materials which may be handled at Petrochem's facility.

- (a). Petrochem's Lemont facility has only had one reportable incident at its facility since its inception in 1983. That incident was the loss of approximately 100 pounds of liquid caustic to the canal in 1985, due to a hose failure near the coupler fitting. The spill was immediately contained and cleaned-up by Petrochem and properly reported to the National Response Center and Illinois Environmental Protection Agency. No significant damage to the environment or risk to human health occurred as a result of this spill Petrochem now over specifies its hoses and couplings for wayside work. All unused couplings are capped.
- (b). Petrochem's tank farm storage area and drum storage area are entirely surrounded by concrete retaining walls to create areas equivalent to 110% of the total rated capacity of the storage vessels. This prevents loss of materials to the canal or soil. The greatest potential for loss of materials lies at the transfer points of materials from vehicles or vessels into the tank farm.

The unloading dock for the drum storage area is designed such that drums once placed on the dock will drain into the storage area within the retaining walls. Should they begin to leak inside of a delivery truck, or spill or rupture before crossing the threshold of the dock, spilled material would be contained in a 200 gallon spill containment/collection sump built into the asphalt drive at the base of the dock.


Lemont/Cook | constic spill/Barge Hose / 28% coursed / 150 gal/Englined | Luptured | 150 gal/Englined | 2/19/85
Chassfurtion of incident Minor

(iii/iv) Transfer areas for the tank trucks or for drums are simple retention basins for spills and precipitation. Drainage is accomplished by manually activated pumps as noted above.

Drainage for the balance of the property (outside of the spill retention or storage containment areas) is to the canal either by direct gradient or by a small ditch on the western portion of the property. (See Attachment E, Facility Drainage Map.) The areas which drain directly to the canal are, for the most part, driveways and parking areas for employee vehicles. The drainage ditch on the western portion of the property has a control gate which can be closed to contain and recover materials in the event materials should appear in or on the surface of the waters. The capacity of the ditch is several thousand gallons.

Because of Petrochem's location below the dike road adjacent to the DesPlaines River, it is subject to frequent seepage along the parking areas of the north side of the property when the river is high. Drainage tiles have been buried to divert this flow around the buildings and towards the barge slip. This water is regarded as having little chance of being contaminated.


- (e) (2) Bulk storage tanks (on shore).
- (i/ii) All of the storage tanks and vessels used inside the facility are constructed of materials compatible with the material held in storage, and are not used to store other materials. Each vessel, except the receiving tanks, is dedicated to a particular type of material. All vessels are located inside of a concrete dike designed to contain 110% of the total capacity of all vessels. (See Attachemnt F, Storage Tank Descriptions).
- (iii) Rainwater which collects inside of the diked area is used as process water in the closed loop barge cleaning system and/or sent to a treatment facility to be cleaned prior to discharge.
- (iv/v) Petrochem does not have any wholly or partially buried tanks for any storage purpose (except the septic system) on its facility.
- (vi) Petrochem's tank farm vessels are subjected to periodic integrity testing on the schedule as noted in Attachment G of this plan. Employees are instructed to be observant for signs or evidence of deterioration, leaks, or accumulation of stored materials inside the diked areas as part of their normal, daily work routine. They are to report any problems which they find to their supervisor immediately.



Refer to the FLOOD INSURANCE RATE MAP EFFECTIVE date shown on this map to determine when actuarial rates apply to structures in the zones where elevations or depths have been established.

THE PERSON NAMED IN COLUMN TWO IS NOT THE PERSON NAMED IN COLUMN TWO IS NAM

To determine if flood insurance is available in this community, contact your insurance agent, or call the National Flood Insurance Program at (800) 638-6620) or (800) 424-8872.



APPROXIMATE SCALE

1000 FEET

NATIONAL FLOOD INSURANCE PROGRAM

FIRM FLOOD INSURANCE RATE MAP

COOK COUNTY, ILLINOIS (UNINCORPORATED AREAS)

PANEL 165 OF 245 (SEE MAP INDEX FOR PANELS NOT PRINTED)

> COMMUNITY-PANEL NUMBER 170054 0165 B

> > EFFECTIVE DATE: **APRIL 15, 1981**

federal emergency management agency federal insurance administration

38

100-Year Flood Boundary Zone Designations® With Date of Identification e.g., 12/2/74 100-Year Flood Boundary

ALD SE

ZONE B

Base Flood Elevation Line With Elevation in Feet**

-513-

Base Flood Elevation in Feet Where Uniform Within Zone** (EL 987)

Elevation Reference Mark

RM7×

. M15

**Referenced to the National Geodetic Vertical Datum of 1929

*EXPLANATION OF ZONE DESIGNATIONS

ZONE

V1-V30

EXPLANATION

Areas of 100-year flood; base flood elevations and flood hazard factors not determined. A

Areas of 100-year shallow flooding where depths are between one (1) and three (3) feet; average depths of inundation are shown, but no flood hazard factors AD

Areas of 100-year shallow flooding where depths are between one (1) and three (3) feet; base flood elevations are shown, but no flood hazard factors are determined. AH

Areas of 100-year flood; base flood elevations and flood hazard factors determined. A1-A30

A99

Areas of 100-year flood to be protected by flood protection system under construction; base flood elevations and flood hazard factors not determined.

Areas between limits of the 100-year flood and 500-year flood; or certain areas subject to 100-year flood-ing with average depths less than one (1) foot or where the contributing drainage area is less than one square mile; or areas protected by levees from the base flood. (Medium shading) 8

C Areas of minimal flooding, (No shading)

Areas of undetermined, but possible, flood hazards. D

Areas of 100-year coastal flood with velocity (wave action); base flood elevations and flood hazard factors not determined.

Areas of 100-year coastal flood with velocity (wave action); base flood elevations and flood hazard factors determined.

NOTES TO USER

Certain areas not in the special flood hazard areas (zones A and V) may be protected by flood control structures.

This map is for flood insurance purposes only; it does not necessarily show all areas subject to flooding in the community or all planimetric features outside special flood hazard areas.

For adjoining map panels, see separately printed Index To Map

INITIAL IDENTIFICATION MAY 27, 1977

FLOOD HAZARD BOUNDARY MAP REVISIONS

FLOOD INSURANCE RATE MAP EFFECTIVE APRIL 15, 1981

FLOOD INSURANCE RATE MAP REVISIONS


69

was a section of the section of the

Appendix A




Appendix B



Appendix C

PHOTOGRAPHS



Photograph locations

Jan	89	
	Jan	Jan 89

ME: 1:00 pm

Photograph by:

Tim Murphy

Location:

Petrochem Services, INC Canal Bank Rd. N.E, Lemont

Comments: Picture taken toward

the west of Waste process storage and treatment area Rob Watson of IEPA on left

Mike Crafton of Heritage Environmental Scrvices on right



DATE: 9 Jan 89

TIME: 1:00 pm

Photograph by:

Tim Murphy

Location: Canal Bank Rd. NE

Lemont, Cook Co. IL

Comments: Picture taken toward

the northwest of truck transfer containment area



DATE:	9	Jan	89	

ME: 1:00 pm

Photograph by:

Tim Murphy

Location:

Petrochem Services, INC

Canal Bank Rd NE, Lemont

Comments: Picture taken toward

the northeast of process

Water storage tanks



3

DATE: 9 Jan 89

TIME: 1:00 pm

Photograph by:

Tim Murphy

Location: Canal Bank Rd. NE

Lemont, Cook Co., IL

Comments: Picture taken toward

the north of waste process

Storage and treatment area,

roll-off boxes and top of

drum crusher can also be

Seen



DATE:	9	Jan	89	
-				

ME: 1:00 pm

Photograph by:

Tim Murphy


Location:

Petrochem Services, INC. Canal Bank Rd. N.E, Lemont

Comments: Picture taken toward
the North Northeast with a

process water storage tank in
foreground and waste

process storage and treatment
area in background



TIME: 1:00 pm

Photograph by:

Tim Murphy


Location: Canal Bank Rd. N.E.

Lemont, Cook Co., IL

Comments: Picture taken toward

the east Northeast with a process water stomge tank in foreground and waste process storage and treatment area in background





DATE:	9	Jan	89	
-		A STATE OF THE PARTY OF THE PAR		

.ME: 1:00 pm

Photograph by:

Tim Murphy

Location:

Petrochem Services INC.

CANAL BANK Rd. N.E. Lemont

the Northwest along diked wall of waste process storage and treatment area, trailer storage area on left



DATE: 9 Jan 89

TIME: 1:00 pm

Photograph by:

Tim Murphy

Location: Canal Bank Rd N.E.

Lemont, Cook Co., IL

Comments: Picture taken toward

the northeast of drainage ditch, trailer storage

area on the right



DATE: 9 Jan 89 .

ME: 1:00 pm

Photograph by:

Tim Murphy

Location:

Petrochem Services INC Canal Bank Rd N.E., Lemont

Comments: Picture taken toward

the south west of drainage ditch going toward Sanitary and ship canal



9

DATE: 9 Jan 89

TIME: 1:00 pm

Photograph by:

Tim Murphy

Location: Canal Bank Rd N.E.

Lemont, Cook Co., IL

Comments: Picture taken toward

the south southeast of

burned shedder unit



DATE: 9 Jan 89

ME: 1:00 pm

Photograph by:

Tim Murphy

Location:

Petrochem Services Inc Canal Bank Rd. N.E., Lemont

The south east of South-

west part of facility, part of burned shedder unit on

left



11

DATE: 9 Jan 89

TIME: 1:00 pm

Photograph by:

Tim Murphy

Location: Canal Bank Rd. N.E.

Lemont, Cook Co., IL

Comments: Picture taken toward

the north west of south
west part of facility
where fixation unit is
to be built, burned
Shedder unit in background



12

DATE: 9 Jan 89

ME: 1:00 pm

Photograph by:

Tim Murphy

Location:

Petrochem Services INC.

Canal Bank Rd. N.E., Lemont


Comments: Picture taken toward

the south southwest accross

sanitary and ship canal

showing fractures in mess

Niagaran dolomite



13

DATE: 9 Jan 89

TIME: 1:00 pm

Photograph by:

Tim Murphy

Location: Canal Bank Rd. N.E.

Lemont, Cook Co., IL

Comments: Picture taken toward

the east wortheast of

drum crushing unit, 15

cubic yard roll-off box

to the right



DATE:	9	Jan	89	

IME: 1:00 pm

Photograph by:

Tim Murphy

Location:

Petrochem Services INC Canal Bank Rd. N.E., Lemont

Comments: Picture taken toward

the north northeast of

the drum storage area



15

DATE: 9 Jan 89

TIME: 1:00pm

Photograph by:

Tim Murphy

Location: Canal Bank Rd. N.E.

Lemont, Cook Co., IL

Comments: Picture taken toward

the Northeast of the drum

Storage area

